MF-3UD/R5



power supply	manual
max. headstay length	37 m
forestay (rod size)	-60, -76
ø forestay (wire)	19 mm
aluminium profiles	R5
stroke stay adjuster	80 mm
boat size	63 - 85 ft.
profile material	aluminum

Furling system for below-deck installation

Drive: Manual, furling line on drum
Connection: Chainplate connection below deck, with deck cut-out


The manual furling systems of the MF series are the continuation of a long tradition of reliable and well-engineered furling systems. Building on more than 30 years of experience with our manual furling systems, this product shows the continuation of both our technical and optical principles:

- uncompromising reliability
- timeless design
- long durability
- low-maintenance operation
- high availability of replacement parts

The **MF-UD** version is designed for **recessed installation** and connects directly to a **chainplate below deck**, through a deck cut-out. Compared to the MF-DF variant with deck flange, this solution offers a simpler installation concept and is ideally suited for yachts where the chainplate is positioned *close* below deck level.

Compared to the classic on-deck MF installation, the MF-UD allows the **tack attachment to be positioned as low as the deck level**. This enables maximum use of the foretriangle and results in improved **aerodynamic efficiency**. At the same time, the deck remains visually uncluttered, emphasizing the clean lines of modern yacht design.

Features



Integrated Turnbuckle

The integrated turnbuckle is designed for precise rig tuning in port. It is housed inside the torque tube and can be easily accessed and adjusted from the outside using simple tools. This allows accurate adjustment of forestay length, rig trim and mast rake while the yacht is docked.



Stainless Steel Drum Guard

The elegant stainless steel drum protection cage prevents the reef line from slipping. It also protects the furling system from damage.



Halyard Swivel FS

The Reckmann high-performance halyard swivels turn with extremely low amounts of friction, thereby guaranteeing a secure operation without twisting the halyard. The compact design and size graduation ensure a low weight aloft.


Find out more about the Reckmann Halyard Swivel FS.

Features



Aluminium profiles

Find out more about the Reckmann aluminium profiles.



Carbon fiber profiles

Find out more about the Reckmann carbon profiles.



To install on the chain plate: MF-UD