UD-2CE



power supply	electric
attachment of the sail	with profile
max. headstay length	23 m
forestay (rod size)	-17, -22, -30, -40
ø forestay (wire)	8 mm, 10 mm, 12 mm
aluminium profiles	R20, R30
carbon profiles	S2, S2.5
stroke stay adjuster	60 mm
mwl tack ring	1,50 t
mwl tack ring HL (opt.)	7,80 t
max. speed	27 U/min
max. drive torque	82 Nm
place of installation	chain plate below deck
weight	10 kg
A	219 mm
B	87 mm
H	185 mm
L	363 mm

Electric furling system for below-deck installation

for chainplate connection through deck cut-out

The Reckmann **UD-CE** is an electric furling system designed for installations with a chainplate connection below deck. The drive unit, gearing and mechanics are located completely below deck, while the forestay is led through a deck opening to the furling system above.

The **UD-CE** system is available in different variants and offers the following key features:

- compact system size
- integrated turnbuckle for forestay length adjustment
- excellent performance-to-weight ratio
- suitable for various types of headstays
- forestay connection above deck level
- compatible with carbon and aluminium foils
- reliable backup system, easy and safe to operate from deck level

The **UD-CE** version is designed for **recessed installation** and connects directly to a **chainplate below deck**, through a deck

cut-out. Compared to the UD-CDFE variant with deck flange, this solution offers a simpler installation concept and is ideally suited for yachts where the chainplate is positioned *close* below deck level.

The **integrated turnbuckle** is designed as a Dockside Adjuster and allows precise adjustment of forestay length, rig trim and mast rake while the yacht is docked. It is housed inside the torque tube and can be accessed and adjusted from the outside using simple tools.

The UD-CE combines a clean deck layout with fully below-deck mechanics and a direct structural load path via the chainplate: A robust and technically elegant solution for yachts with under-deck chainplate arrangements.

Features



Halyard Swivel FS

The Reckmann high-performance halyard swivels turn with extremely low amounts of friction, thereby guaranteeing a secure operation without twisting the halyard. The compact design and size graduation ensure a low weight aloft.

Find out more about the Reckmann Halyard Swivel FS.



Tack Slider

The tack slider or floating tack swivel allows the sail luff to be tensioned independently of the stay. This is a necessary addition, specifically with sails that have a halyard lock.

Find out more about the Reckmann Tack Slider TKS.




Carbon Foils

Our carbon profiles offer high resistance and low weight at the same time. A weight reduction of 50-60 % in comparison with conventional aluminium profiles means that there is a significant improvement in performance.

Find out more about the Reckmann carbon profiles.



UD-CE



Dimensions UD-CE for installation on the chain plate – see table for more information